

Ref. UL file no. R 39831
Partition panel unit with fire resistance

Models:

WP-F 100, WP-F 120, WP-F 140 **1 hour**

WP-F 150, WP-F 160, WP-F 180, WP-F 200, WP-F 240 **2 hours**

Models:

FP-F 100, FP-F 120, FP-F 140 **1 hour**

FP-F 150, FP-F 160, FP-F 180, FP-F 200, FP-F 240 **2 hours**

Head Office/Production Plant::

BRUCHA Gesellschaft m.b.H
 A-3451 Michelhausen · Rusterstraße 33
 tel.: +43 2275 58 75 · fax-DW: 1804
 office@brucha.at

Branch US:

BRUCHA Corp.
 1776 S Jackson Street, Suite 603
 Denver, CO 80210
 tel.: +1 (866) BRUCHA1
 fax: +1 (866) 278-2421
 infousa@brucha.at

Additional installation details:

point 1

check of dimensions and quantity of received panels ref. to the order

point 2

mounting instructions available – www.brucha.com / **download**

point 3

inserting of mineralwool stripes (20 to 30 mm thick) in connecting joints of panels to connecting components

point 4

inserting of fire protection seal (type: Hilti CFS-S Sil) into groove-spring connection of panel joint

point 5

covering of panel connections – joints with flashing – profiles , fixing of them with stainless steel screws or rivets to panels and connecting components

point 6

panel joint **WP-F**

FP-F

